

weight

g/
each



16	3	24 48	240					10	130
----	---	-------	------------	--	--	--	--	----	-----



16	4	24 363	24 364	24 329				10	235
16	5	24 365	24 366	24 142				10	260
32	3	24 367	24 331					10	255
32	4	24 368	24 369	24 330				10	270
32	5	24 370	24 207	24 143				10	300




63	3		24 336				5 1000
63	4		24 337	24 338	24 339		5 1050
63	5			24 134			5 1120



63	3	24 140	24 340	24 145			5 1030
63	4	24 232	24 341	24 035	24 342		5 1060
63	5			24 062		24 320	5 1140



125	3	24 197	24 198	24 220			1 1900
125	4	24 221	24 199	24 200	24 201		1 1920
125	5	24 222		24 202		24 279	1 2020




5 MB 43

AMPERE	16					
POLES	3					
a	56.5					
b	60.0					
c	93.0					
d	73.0					
e	29.5					
f	23.5					
h.Ø	5.5					
i	3.0					
k	M 20					
Conductor.mm² min.	1.5					
Conductor.mm² max.	4					

Surface Mounting Appliance Inlet

- cable entry one at top (open)
- splashproof IP 44




5 MB 44

AMPERE	16		32			
POLES	4	5	3	4	5	
a	72,4	72,4	79,1	79,1	79,1	
b	90,0	90,0	92,0	92,0	92,0	
c	120,0	122,0	134,0	134,0	134,0	
d	84,0	84,0	89,0	89,0	89,0	
e	77,0	77,0	84,0	84,0	84,0	
f	33,5	33,5	30,0	30,0	30,0	
h	9,0	9,0	9,0	9,0	9,0	
i	5,5	5,5	5,5	5,5	5,5	
k	9,0	9,0	9,0	9,0	9,0	
l Ø	21,0	21,0	21,0	21,0	21,0	
m	87,0	87,0	94,0	94,0	94,0	
n	M 20	M 20	M 25	M 25	M 25	
Conductor mm² min.	1,5	1,5	2,5	2,5	2,5	
Conductor mm² max.	4	4	10	10	10	

Surface Mounting Appliance Inlet

- cable entry one at top (open) and one at bottom (closed)
- fixing centers outside
- splashproof IP 44




5 MB 48

AMPERE	63					
POLES	3	4	5			
a	118,0	118,0	118,0			
b	170,0	170,0	170,0			
c	259,0	259,0	259,0			
d	174,0	174,0	174,0			
e	104,0	104,0	104,0			
f	136,0	136,0	136,0			
hØ	6,1	6,1	6,1			
i	6,0	6,0	6,0			
k	M 40	M 40	M 40			
l	M 32/40	M 32/40	M 32/40			
Conductor mm² min.	6	6	6			
Conductor mm² max.	25	25	25			

Surface Mounting Appliance Inlet

- cable entry one at top (open) and two at bottom (closed)
- splashproof IP 44



5 MB 37


AMPERE	63				
POLES	3	4	5		
a	118,0	118,0	118,0		
b	170,0	170,0	170,0		
c	259,0	259,0	259,0		
d	174,0	174,0	174,0		
e	104,0	104,0	104,0		
f	136,0	136,0	136,0		
h Ø	6,1	6,1	6,1		
i	6,0	6,0	6,0		
k	M 40	M 40	M 40		
l	M 32/40	M 32/40	M 32/40		
Conductor mm² min.	6	6	6		
Conductor mm² max.	25	25	25		

Surface Mounting Appliance Inlet

- cable entry one at top (open) and two at bottom (closed)
- nickel plated contacts
- watertight IP 67

Accessories:

Closure cap see page 77/2



5 MB 42

AMPERE	125					
POLES	3	4	5			
a	160,0	160,0	160,0			
b	260,0	260,0	260,0			
c	364,0	364,0	364,0			
d	165,0	165,0	165,0			
e	140,0	140,0	140,0			
f	240,0	240,0	240,0			
hØ	8,3	8,3	8,3			
i	10,0	10,0	10,0			
k	M 50	M 50	M 50			
Conductor mm ² min.	25	25	25			
Conductor mm ² max.	70	70	70			

Surface Mounting Appliance Inlet

- high temperature resistant contact carrier
- box terminals
- nickel plated contacts
- watertight IP 67

Accessories:

Closure cap see page 77/2