


POLES



110 V
50-60 Hz

230 V
50-60 Hz

400 V
50-60 Hz

500 V
50-60 Hz

100-300 Hz
> 50V

301-500 Hz
> 50V

Std Pack

weight

Ampere

Poles

3pol. 4pol. 5pol. 3pol. 4pol. 5pol. 3pol. 4pol. 5pol. 3pol. 4pol. 5pol. 3pol. 4pol. 5pol.
4h 4h 4h 6h 9h 9h 9h 6h 6h 7h 7h 7h 10h 10h 10h 2h 2h 2h

Qty

g/
each



TYP 31 2001

16	3	31 886	31 880					10	175
16	4		31 887	31 881				10	200
16	5			31 2001				10	235
32	3	31 0085	31 882					10	285
32	4		31 0055	31 883				10	300
32	5			31 2002				10	330



TYP 31 30 4

16	3	31 000	31 001	31 002	31 210	31 180	31 179	10	180
16	4	31 003	31 004	31 005	31 006	31 007	31 008	10	205
16	5	31 009	31 010	30 3	31 031	31 098	31 068	10	240
32	3	31 012	31 013	31 014	31 491			10	295
32	4	31 015	31 016	31 017	31 018	31 019	31 020	10	310
32	5	31 021	31 022	30 4	31 023	31 367	31 067	10	345



TYP 31 48

16	3	31 25	31 26	31 27	31 607			10	195
16	4	31 28	31 29	31 30	31 31	31 32	31 33	10	215
16	5	31 34	31 35	31 36	31 225	31 496	31 429	10	250
32	3	31 37	31 38	31 39				10	315
32	4	31 40	31 41	31 42	31 43	31 44	31 45	10	325
32	5	31 46	31 47	31 48	31 295	31 497	31 434	10	360




TYP 31 12

63	3	31 08	31 04	31 09	31 723	31 606		5	940
63	4	31 49	31 50	31 51	31 52	31 085		5	980
63	5	31 53	31 54	31 12	31 086	31 500	31 257	5	1030



TYP 31 821


16	3	31 793	31 0046	31 795	31 796			10	225
16	4	31 797	31 0047	31 0048	31 800	31 802	31 801	10	235
16	5	31 803	31 804	31 851	31 806	31 808	31 807	10	275
32	3	31 809	31 810	31 811	31 812			10	380
32	4	31 813	31 814	31 815	31 816	31 818	31 817	10	400
32	5	31 819	31 820	31 821	31 822	31 824	31 823	10	470

[illegible]

QUICK CONNECT[®]
BY BALS

Connector


- moulded cable sleeve
- screwless 4 point „Klick-Rast“ bayonet system
- screwless terminals
- special contact technique
- further technical informations on page 1
- splashproof IP 44

[illegible]

Connector


- with long cable sleeve
- splashproof IP 44

also available with short
cable sleeve

[illegible]


Connector

- with cable gland
- splashproof IP 44

[illegible]

Connector

- with cable gland
- high temperature resistant contact carrier
- Kontex Plus
- box terminals
- nickel plated contacts
- for cable Ø up to 36,5 mm max
- splashproof IP 44

[illegible]

Connector

- with cable gland
- high-temperature resistant contact-carrier
- nickel-plated contacts
- splashproof IP 55